

AceSeal EZ PRO AC/R DRY

A/C SYSTEM DEHYDRATING AGENT

DESCRIPTION: AceSeal EZ PRO AC/R DRY (ASEZ-DRY) is an A/C drying agent formulated with a dehydrating agent which converts harmful moisture in the system to an inert silicone oil. This oil blends with the a/c lubricating fluid to further enhance lubrication inside the A/C system.

AceSeal EZ PRO AC/R DRY should be used whenever moisture levels in the system exceed generally accepted industry levels (100ppm for POE or 50ppm for Mineral/AB oils.) Always use AceSeal EZ PRO AC/R DRY at least 20 minutes before introducing any AceSeal EZ Leak Stop Pro product into the system if moisture exceeds, or could exceed these levels.

FEATURES & BENEFITS

- **Eliminates Moisture in the System**
- **Quick & Easy Installation**
- **Compatible With All Refrigerants Excluding Ammonia... and All Oils**

DIRECTIONS:

STEP 1: Turn the A/C system on and verify the unit is running. Connect AceSeal EZ PRO AC/R DRY to the low-side service port of the system. This is generally the large line.

STEP 2. Insure the valves on manifold gauge set are closed. Start by connecting the high side (red) line of manifold gauge set to the high side service port. Remove AceSeal EZ PRO AC/R DRY from the Mylar bag and loosely connect the middle manifold hose (yellow) to the 1/4" SAE male fitting of the AceSeal EZ PRO AC/R DRY being careful NOT to depress the Schrader core. Quickly open the high side manifold valve to purge air out of the yellow hose. Now close the high side manifold valve, and quickly tighten the yellow hose fitting to the injector.

STEP 3. Next rapidly open and close the high side valve of the manifold gauge allowing a small amount of liquid to flow through the yellow hose and AceSeal EZ PRO AC/R DRY tube. With high side valve of the manifold gauge set closed, wait one minute for the yellow hose and AceSeal EZ PRO AC/R DRY to equalize to suction pressure. Disconnect AceSeal EZ PRO AC/R DRY from suction service port and from manifold gauge set. Allow unit to run for at least one hour to insure product has circulated in the system. Recycle empty container.

PROFESSIONAL USE ONLY. KEEP OUT OF THE REACH OF CHILDREN.

PACKAGING 6 per case

Refer to product label & Safety Data Sheet for precautionary and First Aid Information. The SDS is available on the ACE website at www.acechempro.com

