

A

**TEFLON TAPE (ATT)  
Thread Sealing Compound**

C

**ACE TEFLON TAPE (ATT)** is a non-toxic, non-flammable, 0.0035 thick tape made from virgin Teflon. Meets or exceeds MIL-T-27730A. Supplied in individual plastic dispenser. **ACE TEFLON TAPE (ATT)** is for use on metal and plastic threaded connections and permits easy disassembly. Suitable for use on oxygen systems. Temperature range between -450°F to +500°F.

E

**FEATURES & BENEFITS**

- Easy to use
- Leak-proof seal.

F

**DIRECTIONS for USE:** Clean oil, dirt, grease or any other foreign matter from threads. Tightly wrap tape three or four times around male threads. Gently inserted male threads into female end. Screw ends tightly together for leak-proof seal.

A

**SAFETY:** Wash hands after use. Do NOT ingest. **KEEP OUT OF THE REACH OF CHILDREN.**

C

**PHYSICAL PROPERTIES**

APPEARANCE	.....	White Tape
COLOR	.....	White
pH	.....	N/A
SPECIFIC GRAVITY	.....	N/A
PACKAGING	.....	100x1/2"x520" per carton

T

Read Material Safety Data Sheet overleaf.

S

**Atlantic Chemical & Equipment Company**  
3471 Atlanta Ind Pkwy Ste 200 Atlanta GA 30331  
Telephone 800 929 2436 Web Address [www.atlanticchemical.com](http://www.atlanticchemical.com)