

MECHANIC'S CHOICE

PENETRANT LUBRICANT
DEMOISTURANT PROTECTANT

ACE MECHANIC'S CHOICE (MCA) is a high solvency, multi-purpose penetrant formulated to rapidly break through dirt, rust and scale to seep into parts that have become frozen or encrusted with corrosion. Long lasting lubrication provides reduced friction. Will not dry out or become brittle. Waterproof seal protects surfaces against water. Dries out and protects wet electrical gear and other moisture sensitive parts

FEATURES & BENEFITS

- Fast-Acting Penetrant – Removes Rust and Corrosion
- Demoisturant – displaces water
- Lubricant – Loosens nuts and bolts
- Protectorant – Prevents moisture and corrosion

DIRECTIONS for USE: To Free Frozen Nuts/Bolts: Apply liberally to frozen nuts, bolts, sliding/rotating parts gears etc. Allow to penetrate into threads then work parts back and forth until working smoothly. Reapply to leave protective film. **To Eliminate Corrosion:** Spray directly on to corroded parts. Allow to penetrate, then remove loosened scale before applying final protective coating. **To Displace Moisture:** For best results, switch off electrical equipment and then thoroughly saturate. Restart once moisture has been eliminated.

SAFETY: EXCESSIVE INHALATION: Remove to fresh air and seek IMMEDIATE Medical help. **INGESTION:** Do not induce vomiting. Seek IMMEDIATE medical help. **SKIN CONTACT:** Remove contaminated clothing. Wash affected skin with soap and water. If irritation persists, seek IMMEDIATE medical help. **EYE CONTACT:** Flush with clean water for fifteen minutes, lifting lower and upper eyelids.

DANGER: Contains Trichloroethylene (79-01-6), Mineral Oil (8042-47-5), Ethylene Glycol Monobutyl Ether (111-76-2) and Carbon Dioxide (124-38-9). Use in well-ventilated areas only. Avoid breathings mists or vapors. Excessive inhalation of vapors may cause nasal/respiratory irritation and central nervous system depression effects including dizziness, nausea and headaches. Vapors in poorly ventilated areas can cause unconsciousness or death. If you experience eye watering, headaches or dizziness, increase airflow, wear respiratory protection or leave the area. Avoid eye or skin contact. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the state of California to cause cancer.

A

C

E

F

A

C

T

S

PHYSICAL PROPERTIES

APPEARANCE	Clear Liquid
ODOR	Solvent
FLASH POINT	~158°F
FLAMMABILITY	Non-Flammable Spray
PROPELLANT	Carbon Dioxide
SPECIFIC GRAVITY	1.25
PACKAGING	6x16-oz (15oz net)/case



**ATLANTIC CHEMICAL & EQUIPMENT COMPANY 3471 Atlanta
Ind Pkwy Ste 200 Atlanta GA 30331**

Telephone 800 929 2436

Web Address www.atlanticchemical.com