

A

C

E

F

A

C

T

S

PIPE KOTE (PKA)

Cold Pipe Aerosol Insulation

ACE PIPE KOTE (PKA) is a durable, flexible, water-resistant, ultra-high texture insulating pipe coating that dries to a clean, white finish. **ACE PIPE KOTE (PKA)** is formulated to provide a "quilting" effect on stainless steel, black iron, brass, copper, galvanized and PVC pipes to stop and prevent condensation build-up and dripping from cold surfaces.

FEATURES & BENEFITS

- Multiple applications - use on cold water pipes, refrigeration and condenser lines, cold air ducts and ice machine coils, etc.
- High texture coating- provides textured "quilting" effect that is paintable and water-resistant.
- Long-lasting coating - prevents condensation and water drip.

DIRECTIONS for USE: Shake can vigorously until ball rattles. Surfaces must be clean and dry. Cover surfaces under area to be treated with newspaper. Spray with sweeping motion from about 10 inches from the surface. Apply in several thin coats. Allow each coat to dry prior to applying next coat. If coating runs, can is too close to surface. Shake can during use. Invert can and spray a few short bursts to clear valve after each use. Dries to touch in 5 minutes, cures fully 24 hours minimum. Coverage 12-15 sq. ft. per can subject to film thickness. Working temperature range 0°F to 100°F.

SAFETY: If inhaled, remove to fresh air. If swallowed, do NOT induce vomiting, seek IMMEDIATE medical help. For skin/eye contact, flush with clean water for 15 minutes, seek IMMEDIATE medical help if irritation persists.

CAUTION: Extremely flammable. Contains Trichloroethylene, Parachlorobenzotrifluoride and LP Gas. Do not use near heat, sparks or flame. Avoid excessive inhalation. Avoid skin/eye contact. Do not store at temperatures above 120°F. Harmful or fatal if swallowed. **KEEP OUT OF THE REACH OF CHILDREN.**

PHYSICAL PROPERTIES

APPEARANCE	Viscous White Liquid
FLAMMABILITY	Extremely Flammable Spray
FLASH POINT	-114°F (T.O.C)
SPECIFIC GRAVITY	1.358
PROPELLANT	LP Gas
NFPA FIRE RATING	Level 2 Aerosol
PACKAGING	6x20oz (net 15oz)/case

