

A  
C  
E  
P  
A  
C  
T  
S

# PAN PATCH (PPA) Condensate Aerosol Pan Sealant

**ACE PAN PATCH (PPA)** is a non-chlorinated, durable, rubberized, flexible spray-on coating designed to seal out rust and corrosion. One can of **ACE PAN PATCH (PPA)** will cover approximately 12-15 sq. ft if applied in two thin coats.

### FEATURES & BENEFITS

- Corrosion resistant formulation - ideal for repairing metal or plastic condensate drain pans.
- Super thick formulation - provides impervious rust and corrosion-proof barrier.
- Super thick, flexible coating - resistant to cracking and peeling.
- Meets MIL Spec TT-C-520-A.
- Non-Chlorinated Formula – withstands temperatures up to 210°F.

**DIRECTIONS for USE:** Apply to clean dry surface. Use at temperatures above 60°F. Spray surface with short, even strokes for 12-14 inches. Several thin coats are better than one heavy coat. After use, invert can and spray short burst to clear nozzle. Product will dry to touch in one hour, full cure 8 hours minimum. Working temperature range 0°F to 210°F.

**SAFETY:** If inhaled, remove to fresh air. If swallowed, do NOT induce vomiting, seek IMMEDIATE medical help. For skin/eye contact, flush with clean water for 15 minutes; seek IMMEDIATE medical help if irritation persists.

**CAUTION:** Extremely flammable. Contains Aliphatic Petroleum Solvent, Toluene, and LP Gas. Do not use near heat, sparks or flame. Avoid excessive inhalation. Avoid skin/eye contact. Do not store at temperatures above 120°F. Harmful or fatal if swallowed. **KEEP OUT OF THE REACH OF CHILDREN.**

### PHYSICAL PROPERTIES

APPEARANCE	....	Viscous Liquid
COLOR	....	Black
ODOR	....	Solvent
FLASH POINT	....	60°F (T.O.C)
SPECIFIC GRAVITY	....	0.940
PROPELLANT	....	LP Gas
VOC CONTENT	....	70%
NFPA FIRE RATING	....	Level 3 Aerosol
PACKAGING	....	6x20oz (net 14oz)/case

