

ROOFSEAL (RSA)

Aerosol Roof Patch & Repair

ACE ROOFSEAL (RSA) is a non-chlorinated, ultra-durable, rubberized aerosol mastic coating formulated to seal water leaks and fill cracks and voids in most roofing surfaces.

Ideal for sealing and repairing on or around asphalt and fiberglass shingles, built-up tar and gravel, single-ply rubberized and granulated roofs, mobile homes, chimney flashings, vents, rooftop A/C units, etc.

FEATURES & BENEFITS

- Unaffected by water - use on wet or dry surfaces.
- Use on most roof surfaces - asphalt, composition tile, slate, felt, wood and metal, etc.
- Easy to use - sprays as liquid, flows into low spots.

DIRECTIONS for USE: Shake well until agitator ball rattles freely and shake can throughout use. Apply several thin coats using a sweeping motion 12-14 inches from surface. Use at temperatures above 60°F. Spray beyond damaged area and feather into surrounding areas with lighter applications. Dries to touch in one hour, full cure 8 hours minimum. Covers 12-15 sq. ft. per can subject to film thickness. Working temperature range 0°F to 500°F.

SAFETY: If inhaled, remove to fresh air. If swallowed, do NOT induce vomiting, seek IMMEDIATE medical help. For skin/eye contact, flush with clean water for 15 minutes. If irritation persists, seek IMMEDIATE medical help.

CAUTION: Extremely flammable. Contains Aliphatic solvents, Toluene and LP Gas. Avoid heat or flame. Use in well-ventilated areas. Avoid skin/eye contact. **KEEP OUT OF THE REACH OF CHILDREN.**

PHYSICAL PROPERTIES

APPEARANCE	Viscous Liquid
COLOR	Black
ODOR FLASH	Solvent
POINT	60°F (T.O.C)
SPECIFIC GRAVITY	0.940
PACKAGING	6x20oz (net 14oz)/case

Atlantic Chemical & Equipment Company,
3471 Atlanta Ind Pkwy Ste 200 Atlanta GA 30331

Telephone 800 929 2436

Web Address www.atlanticchemical.com

A
C
E
R
O
O
F
S
E
A
L